



**NOTE:**

- DO NOT SHORTEN, LENGTHEN, OR MODIFY THE LEADER CABLE. CUTTING THE LEADER CABLE MAY DAMAGE THE DATA DRIVE CIRCUITRY.
- USE UL CLASS 2 DC POWER SUPPLIES ONLY (100W MAX). CONTACT TECHNICAL SUPPORT FOR QUESTIONS REGARDING CUSTOM POWER SUPPLIES.
- USE 0-10V DIMMERS ONLY. CONTACT TECHNICAL SUPPORT FOR RECOMMENDATIONS.
- MULTIPLE RUNS OF eW FLEX SLX CAN BE CONTROLLED BY THE SAME 0-10VDC DIMMER BY CONNECTING MULTIPLE DIMMING ADAPTER KITS IN A DAISY-CHAIN OR STAR CONFIGURATION. REFER TO USER GUIDE OF DIMMING ADAPTER KIT FOR FURTHER DETAIL.

**PHILIPS**

COPYRIGHT © 2007 PHILIPS SOLID-STATE LIGHTING SOLUTIONS. ALL RIGHTS RESERVED. CHROMACORE, CHROMACORE OF THE COLOR, COLOR KINETICS, THE COLOR KINETICS LOGO, COLOR KINETICS THE LEADER IN INTELLIGENT LIGHT, COLORBLAST, COLORBLAZE, COLORBRIGHT, COLORGLASS, COLORPLAY, COLORSCAPE, DIMAND, DIRECT LIGHT, ESSENTIALWHITE, iV, iCOLOR, iCOLOR CODE, INTELLIWHITE, iV, iPLAY, LIGHT BYNETS UNITS, OPTERA, POWERCORE, QUICKPLAY, SAUCE, THE SAUCE LOGO, AND SMARTJUICE ARE EITHER REGISTERED TRADEMARKS OR TRADEMARKS OF PHILIPS SOLID-STATE LIGHTING SOLUTIONS IN THE UNITED STATES AND/OR OTHER COUNTRIES. ALL OTHER BRAND OR PRODUCT NAMES ARE TRADEMARKS OR REGISTERED TRADEMARKS OF THEIR RESPECTIVE OWNERS.

DATA TERMINATOR



PLACE IN DMX LOOP OUT PORT OF  
POWER/DATA SUPPLY WHEN  
REQUIRED (SEE NOTES)

CAT5/RJ45 PINOUT



(M/W FACING PINS)

TITLE:

SYSTEM WIRING DIAGRAM (TYP)

PRODUCTS:

eW FLEX SLX/PS-96 24V/DIMMING ADAPTER KIT

DATE: 7-28-2008

DWG. BY: BHG

SCALE: NTS

REV:

PAGE: 1 OF 1