eW FLEX SLX
(maximum 1 string per PS-96)

LEADER LENGTH: 50 FEET (15 M)

eW FLEX SLX INLINE ADAPTER
ITEM: 107-000008-00

100-240V AC (2A)

PS-96 24V

NOTE:
-PS-96 24V USED FOR ON/OFF CONTROL ONLY. DO NOT USE WITH CONVENTIONAL DIMMING PANEL. CONTACT TECHNICAL SUPPORT FOR DIMMING OPTIONS.
-DO NOT SHORTEN OR LENGTHEN LEADER CABLE. CUTTING THE LEADER CABLE WILL DAMAGE THE DATA DRIVE CIRCUITRY.

PHILIPS

COPYRIGHT © 2007 PHILIPS SOLID-STATE LIGHTING SOLUTIONS. ALL RIGHTS RESERVED. CHROMACORE, CHROMAMIC, CK, THE CK LOGO, COLOR KINETICS, THE COLOR KINETICS LOGO, COLOR KINETICS THE LEADER IN INTELLIGENT LIGHT, COLORBLAST, COLORBLAZE, COLORBURST, COLORCAST, COLORPLAY, COLORSCAPE, DMMAND, DIRECT LIGHT, ESSENTIALWHITE, eW, iCOLOR, iCOLOR COVE, INTELLIWHITE, iW, iPLAYER, LIGHT WITHOUT LIMITS, OPTIBIN, POWERCORE, QUADPLAY, SAUCE, THE SAUCE LOGO, AND SMARTJUICE ARE EITHER REGISTERED TRADEMARKS OR TRADEMARKS OF PHILIPS SOLID-STATE LIGHTING SOLUTIONS IN THE UNITED STATES AND/OR OTHER COUNTRIES. ALL OTHER BRAND OR PRODUCT NAMES ARE TRADEMARKS OR REGISTERED TRADEMARKS OF THEIR RESPECTIVE OWNERS.

DATA TERMINATOR

PLACE IN DMX LOOP OUT PORT OF POWER/DATA SUPPLY WHEN REQUIRED (SEE NOTES)

CAT5/RJ45 PINOUT



(VIEW FACING PINS)

TITLE:	SYSTEM WIRING DIAGRAM (TYP)
PRODUCTS:	eW FLEX SLX/PS-96 24V/ON-OFF ADAPTER
DATE:	7-17-2007
DWG. BY:	BHG
SCALE:	NTS
REV:	
PAGE:	1 OF 1

PHILIPS SOLID-STATE LIGHTING SOLUTIONS 3 BURLINGTON WOODS DRIVE BURLINGTON, MA 01803 TEL 1.888.FULL.RGB (1.888.385.5742) FAX 1.617.482.8610 WWW.COLORKINETICS.COM