

ADDRESSING AND CONTROL:

- ON-BOARD ADDRESSING FEATURES:

- SEQUENTIAL: EACH LIGHT IS UNIQUELY ADDRESSED AND REQUIRES 3 CONSECUTIVE DMX CHANNELS.
- ALL SAME ADDRESS: ALL FIXTURES ARE CONTROLLED BY 3 CONSECUTIVE DMX CHANNELS.
- SEE USER GUIDE FOR GROUP ADDRESSING FUNCTIONS
- iPLAYER 3 SUPPORTS 340 LIGHT ADDRESSES (2 PORTS)

NOTE:

- USE A THIRD PARTY DMX REPEATER ON EVERY 32nd PDS UNIT IN A CHAIN, OR WHEN THE TOTAL DMX DATA RUN EXCEEDS 1,000 FEET. REFER TO THE USITT DMX-512 STANDARD FOR MORE INFORMATION.
- MAXIMUM NUMBER OF LIGHTS PER PDS-60ca 24V: 20.
- DO NOT SHORTEN OR LENGTHEN LEADER CABLE. CUTTING THE LEADER CABLE WILL DAMAGE THE DATA DRIVE CIRCUITRY.
- iPLAYER 3 CAN SUPPORT TWO SEPARATE DMX UNIVERSES. USE "DMX 1" FOR SINGLE UNIVERSE APPLICATIONS. REFER TO iPLAYER 3 USER GUIDE FOR ADDITIONAL ON-BOARD FEATURES.

PHILIPS


COPYRIGHT © 2007 PHILIPS SOLID-STATE LIGHTING SOLUTIONS. ALL RIGHTS RESERVED. CHROMACORE, CHROMA-MARK, CC, THE CC LOGO, COLOR KINETICS, THE COLOR KINETICS LOGO, COLOR KINETICS THE LEADER IN INTELLIGENT LIGHT, COLORBLAST, COLORBLAZE, COLORBURST, COLORCAST, COLORPLAY, COLORSCAPE, DIMAND, DIRECT LIGHT, ESSENCE, iPLAYER, iPLAYER 3, iCOLOR COVE, INTELLIWHITE, iV-PLAYER, LIGHT WITHOUT LIMITS, OPTIMA, POWERCORE, QUIETPLAN, SAUCE, THE SAUCE LOGO, AND SMARTLITE ARE EITHER REGISTERED TRADEMARKS OR TRADEMARKS OF PHILIPS SOLID-STATE LIGHTING SOLUTIONS IN THE UNITED STATES AND/OR OTHER COUNTRIES. ALL OTHER BRAND OR PRODUCT NAMES ARE TRADEMARKS OR REGISTERED TRADEMARKS OF THEIR RESPECTIVE OWNERS.

DATA TERMINATOR



PLACE IN DMX LOOP-OUT PORT OF POWER/DATA SUPPLY WHEN REQUIRED (SEE NOTES)

CAT5/RJ45 PINOUT



TITLE: SYSTEM WIRING DIAGRAM (TYP)

PRODUCTS: iCOLOR COVE QL/sPDS-60ca 24V DMX/ETHERNET/ iPLAYER 3/ CONTROLLER KEYPAD

DATE: 3-6-2008
 DWG. BY: BHG
 SCALE: NTS
 REV:
 PAGE: 1 OF 1